



CITY OF MURPHY
FLATWORK AND DRIVEWAY
PERMIT REQUIREMENTS

1. Complete and submit a permit application.
2. Submit two (2) site plans (a survey plat is required) showing the location of the flat work or driveway, with respect to the property lines, easements and house.
3. Permit fee- See Murphy Code of Ordinances, Article A9.000 Building, Construction and Development Related Fees

Flat Work
(Sidewalks, patios, etc.)

1. 4" thick slab
2. Reinforcing Steel – No. 3 bars at 24" centers both ways.
3. Expansion joint placed where new work abuts existing concrete or adjacent to foundations.
4. Concrete shall be a minimum of 3000 psi chairs required under pavement.
5. Dowel into existing concrete.
6. Chairs must support mat.

Driveways

1. Reinforcing Steel - No. 3 bars at 24" o.c. both ways.
2. Expansion joint placed where new work abuts existing concrete or adjacent to walls, foundation, curbs, etc.
3. Concrete shall be a minimum of 3000 psi.
4. Chairs are required under rebar.
5. Redwood is required at property line.
6. Concrete at approach must be a minimum of 6" thick.
7. Concrete on property must be a minimum of 4" thick.
8. Minimum 5' radius at approach where adjacent to curb.
9. Dowel into existing concrete.